#### **OPN-CHEMIE OTTO PETRI GmbH**

Produktion techn. Aerosole - Sprays In der Au 14, D-57290 Neunkirchen / Germany

Phone: +49 (0) 27 35 / 77 25-0 Fax: +49 (0) 27 35 / 77 25-90

www.opn-chemie.de info@opn-chemie.de



# **Product Information**

# **OPN-Silicone Grease Spray**

- highly resilient
- long-time effective

### **Properties:**

- bright, high performance lubricant with good adhesion
- very long life
- high friction, lubrication and protection ability
- good corrosion protection displaces water
- prevents squeaking and creaking in many plastic, steel and stainless steel parts etc.
- keeps rubber lips and seals supple and protects against aging and freezing
- temperature resistant up to about +240°C

#### **Application areas:**

versatile application - where conventional lubricants are not sufficient

## **Application:**

Our information are recommendations based on our experience. We accept no liability for any damage without tests concerning suitability for the specific application, without preliminary trials and if the product is misused. Shake can well before use. Clean the parts to be treated, then spray targeted. Do <u>NOT</u> use if parts should be treated afterwards (painted, galvanized, printed, etc.). After evaporation of the solvent OPN Silicone Grease Spray is fully effective and receives its final structure. Avoid that the substance gets on the ground - danger of slipping!

Only for professional use! Always observe safety data sheet before use.

Delivery information: Art.-No. 60355

Spray: 400 ml Content, Packing Unit: 12 Cans/Carton

Observe the information on the label and of the EC-safety data sheet!

Our technical information has been compiled carefully to the best of our knowledge. Because of the many possible influences during processing and use of the products they do not relieve the processor of its own, conscientious exams! A legally binding assurance of certain properties or of the suitability for a particular purpose can not be derived from our information. Existing laws and regulations must be checked and observed from the processor of our products before use in his own responsibility.