OPN-CHEMIE OTTO PETRI GmbH

Produktion techn. Aerosole - Sprays In der Au 14, D-57290 Neunkirchen / Germany

Phone: +49 (0) 27 35 / 77 25-0 Fax: +49 (0) 27 35 / 77 25-90

www.opn-chemie.de info@opn-chemie.de



Product Information

OPN-Long Term Adhesive Lubricant Spray partly synthetic extreme lubricant

- centrifugal resistant
- pressure resistant
- tough adhesive
- high capable of creep

Properties:

- extreme lubricant, light, on partly synthetic base
- centrifugal resistant, tough adhesive, high capable of creep
- water and salt water repellent
- creeps into tiny spaces
- good corrosion protection
- temperature resistant from -35 ° C to about 130 ° C for a short time up to + 200 ° C
- employ many o-rings

Application Range:

 used for ball and roller bearings, high speed chains, also motorcycle chains, gears and worm gears, wire ropes etc.

Application:

Our information are recommendations based on our experience. We accept no liability for any damage without tests concerning suitability for the specific application, without preliminary trials and if the products is misused. Shake can well before use, clean parts, spray targeted from a distance of about 20 cm, extreme adhesion after evaporation of solvent.

Only for professional use! Always observe safety data sheet before use.

Delivery information: Art.-No. 61310

Spray: 400 ml Content, Packing Unit: 12 Cans/Carton

Observe the information on the label and of the EC-safety data sheet!

Our technical information has been compiled carefully to the best of our knowledge. Because of the many possible influences during processing and use of the products they do not relieve the processor of its own, conscientious exams! A legally binding assurance of certain properties or of the suitability for a particular purpose can not be derived from our information. Existing laws and regulations must be checked and observed from the processor of our products before use in his own responsibility.