#### **OPN-CHEMIE OTTO PETRI GmbH**

Produktion techn. Aerosole - Sprays In der Au 14, D-57290 Neunkirchen / Germany

Phone: +49 (0) 27 35 / 77 25-0 Fax: +49 (0) 27 35 / 77 25-90

www.opn-chemie.de info@opn-chemie.de



## **Product Information**

# OPN-Aluminium Spray shiny metallic - mirror finish -

• heat resistant corrosion protection

### **Properties:**

- heat resistant corrosion protection for a lot of metal surfaces
- temperature resistance of aluminum pigments contained up to about +600°C
- provides against weather influences
- fast drying

### **Application Range:**

- as corrosion protection in industry and crafts
- air conditioning and ventilation equipment
- for visual upgrading of zinc and zinc dust coatings etc.

#### Application:

Our information are recommendations based on our experience. We accept no liability for any damage without tests concerning suitability for the specific application, without preliminary trials and if the product is misused. The can should be at room temperature and only be sprayed in good ventilated areas. Before each use shake can well for 2 minutes until the stirring ball moves freely. Try and test on similar surface for material compatibility. Remove rust and degrease the surface thoroughly and spray crosswise at a distance of 20 to 30 cm. In case of several layers let it dry for 5 minutes before spraying the next layer. Self cleaning nozzle. Only for professional use! Always observe safety data sheet before use.

Delivery information: Art.-No. 63010

Spray: 400 ml Content, Packing Unit: 12 Cans/Carton

Observe the information on the label and of the EC-safety data sheet!

Our technical information has been compiled carefully to the best of our knowledge. Because of the many possible influences during processing and use of the products they do not relieve the processor of its own, conscientious exams! A legally binding assurance of certain properties or of the suitability for a particular purpose can not be derived from our information. Existing laws and regulations must be checked and observed from the processor of our products before use in his own responsibility.