

Printing date 17.05.2023 Version number 72 (replaces version 71) Revision: 17.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

. Trade name: OPN-Pickling-Spray

·Article number: 60749

- · Unique formula identifier (UFI): GK7E-F585-400R-KFDV
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint remover
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

**OPN-CHEMIE GmbH** 

In der Au 14

57290 Neunkirchen

www.opn-chemie.de

· Further information obtainable from:

Barbara Angelika Gros-Petri

E-Mail (competent person) baerbel.petri@opn-chemie.de

· 1.4 Emergency telephone number:

Emergency information service Vergiftungs-Informations-Zentrale Freiburg +49 (0) 761 / 1 92 40

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





- · Signal word Danger
- · Hazard-determining components of labelling:

acetone

n-butyl acetate

1-methoxy-2-propanol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date 17.05.2023 Version number 72 (replaces version 71) Revision: 17.05.2023

Trade name: OPN-Pickling-Spray

	(Contd. of page 1)
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours or spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves / eye protection / face protection.
P305+P351+P338	B IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122°F.
P501	Dispose of contents / container in accordance with national regulations of the disposal.
· Additional infor	mation:

EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1A, H220; Press. Gas (Comp.), H280			
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone	25-<50%		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate  Flam. Liq. 3, H226; STOT SE 3, H336, EUH066			
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-methoxy-2-propanol Flam. Liq. 3, H226;  STOT SE 3, H336	5-<10%		
CAS: 108-94-1 EINECS: 203-631-1 Reg.nr.: 01-2119453616-35-xxxx	cyclohexanone Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	<3%		
CAS: 112-34-5 EINECS: 203-961-6 Reg.nr.: 01-2119475104-44-xxxx	2-(2-butoxyethoxy)ethanol  Eye Irrit. 2, H319	2.5-<5%		
CAS: 64-18-6 EINECS: 200-579-1	formic acid  Acute Tox. 3, H331; Skin Corr. 1A, H314; Acute Tox. 4, H302  Specific concentration limits: Skin Corr. 1A; H314: C≥90 %  Skin Corr. 1B; H314: 10 % ≤ C < 90 %  Skin Irrit. 2; H315: 2 % ≤ C < 10 %  Eye Irrit. 2; H319: 2 % ≤ C < 10 %	0.1-<1%		

(Contd. on page 3)

Printing date 17.05.2023 Version number 72 (replaces version 71) Revision: 17.05.2023

Trade name: OPN-Pickling-Spray

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

Dizziness

Dizziness

Nausea

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary oedema.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Fire-extinguishing powder

Carbon dioxide

Use fire extinguishing methods suitable to surrounding conditions.

Foam

- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### **SECTION 6: Accidental release measures**

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 17.05.2023 Version number 72 (replaces version 71) Revision: 17.05.2023

Trade name: OPN-Pickling-Spray

See Section 13 for disposal information.

(Contd. of page 3)

### **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

#### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

<b>SECTION 8: Ex</b>	nosure controls/	nersonal	protection
DECTION O. LA	DOSUIT COLLUIS	personar	protection

8.2	Exposure	controls
U.2	LADUSUI	

- 8.2 Exposure controls						
· Ingredients with limit values that require monitoring at the workplace:						
CAS: 115-10-6 dimethyl ether						
WEL Short-term value: 958 mg/m³, 500 ppm						
Long-term value: 766 mg/m³, 400 ppm						
CAS: 67-64-1 acetone						
WEL Short-term value: 3620 mg/m³, 1500 ppm						
Long-term value: 1210 mg/m³, 500 ppm						
CAS: 123-86-4 n-butyl acetate						
WEL Short-term value: 966 mg/m³, 200 ppm						
Long-term value: 724 mg/m³, 150 ppm						
CAS: 107-98-2 1-methoxy-2-propanol						
WEL Short-term value: 560 mg/m³, 150 ppm						
Long-term value: 375 mg/m³, 100 ppm						
Sk						
CAS: 108-94-1 cyclohexanone						
WEL Short-term value: 82 mg/m³, 20 ppm						
Long-term value: 41 mg/m³, 10 ppm Sk, BMGV						
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol						
WEL Short-term value: 101.2 mg/m³, 15 ppm						
Long-term value: 67.5 mg/m³, 10 ppm						
CAS: 64-18-6 formic acid						
WEL Long-term value: 9.6 mg/m <sup>3</sup> , 5 ppm						
· DNELs						
CAS: 67-64-1 acetone						
Oral DNEL 62 mg(kg (ME)						
Inhalative DNEL 200 mg/m³ (ME)						

(Contd. on page 5)

Printing date 17.05.2023 Version number 72 (replaces version 71) Revision: 17.05.2023

Trade name: OPN-Pickling-Spray

(Contd. of page 4)

#### · Ingredients with biological limit values:

### CAS: 108-94-1 cyclohexanone

BMGV 2 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: cyclohexanol

- · Additional information: The lists valid during the making were used as basis.
- **Appropriate engineering controls** No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

- · Recommended filter device for short term use: Filter AX
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

(EN 374)

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.7$  mm

· Penetration time of glove material

>60 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

≥10 min

· Eye/face protection

(EN 166)



Tightly sealed goggles

 $\cdot \ Body \ protection:$ 

Solvent resistant protective clothing

(EN 13034-6)

Protective work clothing

### **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Odour:
Aerosol
Pink
Acetone-like

• Odour threshold: Not determined.

(Contd. on page 6)

Version number 72 (replaces version 71) Printing date 17.05.2023 Revision: 17.05.2023

Trade name: OPN-Pickling-Spray

	(Contd. of pag
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	Not applicable, as aerosol.
Flammability	Not applicable.
Lower and upper explosion limit	••
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable, as aerosol.
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	110t determined.
water:	Not miscible or difficult to mix.
	Not determined.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	not determined.
Density and/or relative density	0.76766 / 3
Density at 20 °C:	0.76766 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health and	d
environment, and on safety.	
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Solvent separation test:	
Organic solvents:	96.4 %
Water:	1.7 %
VOC (EC)	749.8 g/l
Solids content:	0.0 %
Change in condition	0.0 /0
Evaporation rate	Not applicable.
•	
Information with regard to physical hazard classe	
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container:
0.111.1	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
OT Zame Del Values	
Corrosive to metals	Void

Printing date 17.05.2023 Version number 72 (replaces version 71) Revision: 17.05.2023

Trade name: OPN-Pickling-Spray

(Contd. of page 6)

• Desensitised explosives Void

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD50 LD50 LC50/4 h 10-6 dime LC50/4 h 4-1 aceton LD50 LD50 LC50/4 h	7 Estimates) 51,223 mg/kg (rat) 31,635 mg/kg (rabbit) >183 mg/l (rat)  thyl ether 308 mg/l (rat)  109 109 109 109 109 109 109 109 109 10
LD50 LC50/4 h 10-6 dime LC50/4 h 4-1 aceton LD50 LD50 LC50/4 h	31,635 mg/kg (rabbit) >183 mg/l (rat)  thyl ether  308 mg/l (rat)  te  5,800 mg/kg (rat) 20,000 mg/kg (rabbit)
10-6 dime LC50/4 h 4-1 aceton LD50 LD50 LC50/4 h	>183 mg/l (rat)  thyl ether 308 mg/l (rat)  the 5,800 mg/kg (rat) 20,000 mg/kg (rabbit)
10-6 dime LC50/4 h 4-1 aceton LD50 LD50 LC50/4 h	thyl ether 308 mg/l (rat)  te 5,800 mg/kg (rat) 20,000 mg/kg (rabbit)
LC50/4 h 4-1 aceton LD50 LD50 LC50/4 h	308 mg/l (rat)  100 100 100 100 100 100 100 100 100 1
<b>4-1 aceton</b> LD50 LD50 LC50/4 h	5,800 mg/kg (rat) 20,000 mg/kg (rabbit)
LD50 LD50 LC50/4 h	5,800 mg/kg (rat) 20,000 mg/kg (rabbit)
LD50 LC50/4 h	20,000 mg/kg (rabbit)
LC50/4 h	
	~76 mg/l (rat)
06 4 1	
50-4 n-Du	tyl acetate
LD50	13,100 mg/kg (rat)
LD50	>5,000 mg/kg (rabbit)
LC50/4 h	>21 mg/l (rat)
98-2 1-me	thoxy-2-propanol
LD50	5,660 mg/kg (rat)
LD50	13,000 mg/kg (rabbit)
LC50/4 h	14,700 mg/l (rat)
94-1 cyclo	hexanone
LD50	1,535 mg/kg (rat)
LD50	948 mg/kg (rabbit)
LC50/4 h	>6.2 mg/l (rat)
34-5 2-(2-	butoxyethoxy)ethanol
LD50	5,660 mg/kg (rat)
LD50	4,000 mg/kg (rabbit)
8-6 formic	e acid
LD50	1,100 mg/kg (rat)
LC50/4 h	7.85 mg/l (rat)
L L 1	D50 D50 C50/4 h <b>8-2 1-me</b> D50 D50 D50 D50 D50 D50 D50 D50 D50 D50

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.

(Contd. on page 8)

Printing date 17.05.2023 Version number 72 (replaces version 71) Revision: 17.05.2023

**Trade name: OPN-Pickling-Spray** 

(Contd. of page 7)

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

	OBT 1	1 4 F	<b>Cransport</b>	• •	4.
RI AND I		<b>/</b> • ·	ranchart	Into	rmation

. 1	141	IIN	number	or ID	number
	4.1		number	or 11 <i>)</i>	number

· ADR/RID/ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR/RID/ADN UN1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- · ADR/RID/ADN



· Class 2 5F Gases.

· Label 2.1

(Contd. on page 9)

Printing date 17.05.2023 Version number 72 (replaces version 71) Revision: 17.05.2023

Trade name: OPN-Pickling-Spray

	(Contd. of page 8)
· IMDG, IATA	
· Class · Label	2.1 Gases. 2.1
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
<ul> <li>· 14.6 Special precautions for user</li> <li>· Hazard identification number (Kemler code):</li> <li>· EMS Number:</li> <li>· Stowage Code</li> <li>· Segregation Code</li> </ul>	Warning: Gases.  F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class
· 14.7 Maritime transport in bulk according to IMC instruments	2.  O  Not applicable.
· Transport/Additional information:	11
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	1L Code: E0 Not permitted as Excepted Quantity 2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- $\cdot$  Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS

(Contd. on page 10)

Printing date 17.05.2023 Version number 72 (replaces version 71) Revision: 17.05.2023

Trade name: OPN-Pickling-Spray

(Contd. of page 9)

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product Safety department.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· \* Data compared to the previous version altered.

-GB