

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Long Term Adhesive Lubricant Spray - with PTFE -

Version number: 5.0
Revision: 2023-02-20

Date of compilation: 2015-03-17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifier Trade name	OPN-Long Term Adhesive Lubricant Spray - with PTFE -
	Unique formula identifier (UFI)	V5TF-W5WU-G00U-YP7D
	Other means of identification Article number	61315
	Tariff No.	34039900
1.2	Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses	Industrial use Professional use Consumer use (private households)
	Sector of use Uses advised against	Corrosion inhibiting adhesive lubricant with PTFE Do not use for products which come into contact with foodstuffs
1.3	Details of the supplier of the safety data sheet OPN-CHEMIE GmbH In der Au 14 57290 Neunkirchen www.opn-chemie.de Competent person responsible for the safety data sheet e-mail (competent person)	Barbara Angelika Gros-Petri baerbel.petri@opn-chemie.de
1.4	Emergency telephone number Emergency information service	Poison Information Center Freiburg +49(0)761/19240

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Hazard class and category	Hazard statement
2.3	Aerosols	Aerosol 1	H222,H229
3.2	Skin corrosion/irritation	Skin Irrit. 2	H315
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	STOT SE 3	H336
4.1C	Hazardous to the aquatic environment - chronic hazard	Aquatic Chronic 3	H412

Remarks

For full text of abbreviations: see SECTION 16
The most important adverse physicochemical, human health and environmental effects
Spillage and fire water can cause pollution of watercourses.

- 2.2 Label elements
Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word Danger

Pictograms

GHS02, GHS07



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Long Term Adhesive Lubricant Spray - with PTFE -

Version number: 5.0
Revision: 2023-02-20

Date of compilation: 2015-03-17

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.
P302+P352 IF ON SKIN: Wash with plenty of water.
P312 Call a POISON CENTER/doctor if you feel unwell.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P501 Dispose of contents / container in accordance with national regulations of the disposal.

Additional labelling requirements

Buildup of explosive mixtures possible without sufficient ventilation.

Hazardous ingredients for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics,
<5% n-hexane

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients





3.1 Substances

Not relevant (mixture).

3.2 Mixtures

Description of the mixture

Mixture of substances listed below with nonhazardous additions

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Butane	CAS No 106-97-8 EC No 203-448-7 REACH Reg. No 01-2119474691- 32-xxxx	25 – < 50	Flam. Gas 1A / H220 Press. Gas L / H280	
Propane	CAS No 74-98-6 EC No 200-827-9 REACH Reg. No 01-2119486944- 21-xxxx	10 – < 25	Flam. Gas 1A / H220 Press. Gas C / H280	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC No 921-024-6 REACH Reg. No 01-2119475514- 35-xxxx	10 – < 25	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	
Isobutane	CAS No 75-28-5 EC No 200-857-2 REACH Reg. No 01-2119485395- 27-xxxx	1 – < 5	Flam. Gas 1A / H220 Press. Gas C / H280	

3.3 Remarks

For full text of abbreviations: see SECTION 16

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Long Term Adhesive Lubricant Spray - with PTFE -

Version number: 5.0
Revision: 2023-02-20

Date of compilation: 2015-03-17

SECTION 4: First aid measures

- 4.1 Description of first aid measures
General notes
Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.
Following inhalation
If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.
Following skin contact
Wash with plenty of soap and water.
Following eye contact
Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
Following ingestion
Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.
- 4.2 Most important symptoms and effects, both acute and delayed
Narcotic effects.
- 4.3 Indication of any immediate medical attention and special treatment needed
none

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
Suitable extinguishing media
Water spray. BC-powder.
Unsuitable extinguishing media
Water jet.
- 5.2 Special hazards arising from the substance or mixture
In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.
Hazardous combustion products
Carbon monoxide (CO). Carbon dioxide (CO₂).
- 5.3 Advice for firefighters
In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
For non-emergency personnel
Remove persons to safety.
For emergency responders
Wear breathing apparatus if exposed to vapours/dust/spray/gases.
- 6.2 Environmental precautions
Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.
- 6.3 Methods and material for containment and cleaning up
Advice on how to contain a spill
Covering of drains.
Other information relating to spills and releases
Place in appropriate containers for disposal. Ventilate affected area.
- 6.4 Reference to other sections
Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Long Term Adhesive Lubricant Spray - with PTFE -

Version number: 5.0
Revision: 2023-02-20

Date of compilation: 2015-03-17

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Recommendations
Measures to prevent fire as well as aerosol and dust generation
Use local and general ventilation. Use only in well-ventilated areas.
Advice on general occupational hygiene
Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingsuffs.
- 7.2 Conditions for safe storage, including any incompatibilities
Managing of associated risks
Storage class (LGK)
2 B
- Flammability hazards
- Do not spray on an open flame or other ignition source. Protect from sunlight.
Consideration of other advice
- Packaging compatibilities
- Only packagings which are approved (e.g. acc. to ADR) may be used.
- 7.3 Specific end use(s)
No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
National limit values
Occupational exposure limit values (Workplace Exposure Limits)
this information is not available
Relevant DNELs/DMELs/PNECs and other threshold levels
Relevant DNELs of components of the mixture

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		DNEL	2,035 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		DNEL	773 mg/kg bw/day	Human, dermal	Worker (industry)	Chronic - systemic effects

- 8.2 Exposure controls
Appropriate engineering controls
General ventilation.
Individual protection measures (personal protective equipment)
Eye/face protection
Do not spray in eyes. If required use tight-fitting goggles.
Skin protection
Hand protection
Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.
Type of material
NBR: acrylonitrile-butadiene rubber.
Material thickness
> 0,7 mm

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Long Term Adhesive Lubricant Spray - with PTFE -

Version number: 5.0
Revision: 2023-02-20

Date of compilation: 2015-03-17

Breakthrough times of the glove material

>480 minutes (permeation: level 6)

Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

Operate if possible out of doors or in a well-ventilated place. In case of inadequate ventilation wear respiratory protection. Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Aerosol (Spray aerosol)
Colour	Yellowish brown
Odour	Like lemon
Initial boiling point and boiling range	Not applicable, as aerosol.*
Flammability (solid, gas)	flammable aerosol in accordance with GHS criteria
Explosive limits	0.6 vol% - 15 vol%
Flash point	Not applicable, as aerosol.*
Water solubility	Insoluble
Vapour pressure	3.8 bar at 20 °C 6.8 bar at 50 °C
Density	0.64 g/ml at 20 °C

9.2 Other information

Other safety characteristics

* The finished mixture in an aerosol container is formed after addition of propellant. Several details are not measurable in an hermetic closed, pressurized container.

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

Physical stresses which might result in a hazardous situation and have to be avoided

High temperatures.

10.5 Incompatible materials

Oxidisers.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Long Term Adhesive Lubricant Spray - with PTFE -

Version number: 5.0
Revision: 2023-02-20

Date of compilation: 2015-03-17

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

• Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

• Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Ordinance on systems for handling water-polluting substances (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK (Germany) 2, obviously hazardous to water

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		EL50	12 mg/l	Aquatic invertebrates	24 h
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		EC50	0.23 mg/l	Aquatic invertebrates	21 d

12.2 Persistence and degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		Oxygen depletion	83 %	16 d		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Long Term Adhesive Lubricant Spray - with PTFE -

Version number: 5.0
Revision: 2023-02-20

Date of compilation: 2015-03-17

12.3 Bioaccumulative potential

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Butane	106-97-8		1.09 (pH value: 7, 20 °C)	
Propane	74-98-6		1.09 (pH value: 7, 20 °C)	
Isobutane	75-28-5		1.09 (pH value: 7, 20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0,1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

15 01 04 Metallic packaging

15 01 10 Packaging containing residues of or contaminated by dangerous substances

16 05 04 Containing hazardous gases in pressure containers (including halons)

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN

UN
1950

IMDG-Code

UN
1950

ICAO-TI

UN
1950

14.2 UN proper shipping name

ADR/RID/ADN

AEROSOLS

IMDG-Code

AEROSOLS

ICAO-TI

Aerosols, flammable

14.3 Transport hazard class(es)

ADR/RID/ADN

2
(2.1)

IMDG-Code

2.1

ICAO-TI

2.1

14.4 Packing group

Not assigned

14.5 Environmental hazards

Non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Long Term Adhesive Lubricant Spray - with PTFE -

Version number: 5.0
Revision: 2023-02-20

Date of compilation: 2015-03-17

- 14.7 Maritime transport in bulk according to IMO instruments
The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) Additional information

Classification code 5F

Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625

Excepted quantities (EQ) E0

Limited quantities (LQ) 1 L

Transport category (TC) 2

Tunnel restriction code (TRC) D

International Maritime Dangerous Goods Code (IMDG) Additional information

Marine pollutant -

Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0

Limited quantities (LQ) 1 L

EmS F-D, S-U

Stowage category -

International Civil Aviation Organization (ICAO-IATA/DGR) Additional information

Danger label(s) 2.1



Special provisions (SP) A145, A167

Excepted quantities (EQ) E0

Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

none of the ingredients are listed

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

none of the ingredients are listed

Directive 75/324/EEC relating to aerosol dispensers

Classification of the gas/aerosol Extremely flammable

Labelling Keep out of reach of children. Pressurized container: may burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F.

Additional information -

Industrial Emissions Directive (IED)

VOC content 74.87 %

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Long Term Adhesive Lubricant Spray - with PTFE -

Version number: 5.0
Revision: 2023-02-20

Date of compilation: 2015-03-17

National regulations (Germany)

Ordinance on systems for handling water-polluting substances (Ordinance on facilities for handling substances hazardous to water)(AwSV)

Water hazard class 2 (obviously hazardous to water)

Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	Organic substances		≥ 25 wt%	0.5 kg/h	50 mg/m ³	3)

Notation

3) A total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)

Storage class (LGK) 2 B (Aerosol dispensers and lighters)

National inventories

Country	Inventory	Status
EU	REACH Reg.	Not all ingredients are listed

Legend

REACH Reg. REACH registered substances

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Indication of changes (revised safety data sheet)

Alignment to regulation. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Einfügung: UFI: V5TF-W5WU-G00U-YP7D

16.2 Abbreviations and acronyms

ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road).
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN).
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard.
Asp. Tox.	Aspiration hazard.
BCF	Bioconcentration factor.
BOD	Biochemical Oxygen Demand.
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
COD	Chemical oxygen demand.
DGR	Dangerous Goods Regulations (see IATA/DGR).
DMEL	Derived Minimal Effect Level.
DNEL	Derived No-Effect Level.
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval.
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
EINECS	European Inventory of Existing Commercial Chemical Substances.
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms.
ELINCS	European List of Notified Chemical Substances.
EmS	Emergency Schedule.
Flam. Gas	Flammable gas.
Flam. Liq.	Flammable liquid.
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.
IATA	International Air Transport Association.
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA).
ICAO	International Civil Aviation Organization.
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air.
IMDG	International Maritime Dangerous Goods Code.
IMDG-Code	International Maritime Dangerous Goods Code.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Long Term Adhesive Lubricant Spray - with PTFE -

Version number: 5.0
Revision: 2023-02-20

Date of compilation: 2015-03-17

LGK	Lagerklasse (storage class according to TRGS 510, Germany).
Log KOW	n-Octanol/water.
NLP	No-Longer Polymer.
PBT	Persistent, Bioaccumulative and Toxic.
PNEC	Predicted No-Effect Concentration.
Press. Gas	Gas under pressure.
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals.
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
Skin Corr.	Corrosive to skin.
Skin Irrit.	Irritant to skin.
STOT SE	Specific target organ toxicity - single exposure.
SVHC	Substance of Very High Concern.
TRGS	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).
VOC	Volatile Organic Compounds.
VPvB	Very Persistent and very Bioaccumulative.

16.3 Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN).
International Maritime Dangerous Goods Code (IMDG).
Dangerous Goods Regulations (DGR) for the air transport (IATA).

16.4 Classification procedure

Physical and chemical properties. The classification is based on tested mixture.
Health hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

16.5 List of relevant phrases (code and full text as stated in section 2 and 3)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.