



Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 1

Revision: 10.12.2024

1 Identification of the substance/mixture and of the company/undertaking

· **Product identifier**

· **Trade name:** OPN-PTFE-Spray

· **Article number:** 61450

· **UFI:** 6S5G-853E-U00N-9RW3

· **Relevant identified uses of the substance or mixture and uses advised against**

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Application of the substance / the mixture** Lacquer

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

OPN-CHEMIE GmbH

In der Au 14

57290 Neunkirchen

www.opn-chemie.de

· **Further information obtainable from:**

Barbara Angelika Gros-Petri

E-Mail (competent person) baerbel.petri@opn-chemie.de

· **Emergency telephone number:**

Emergency information service Vergiftungs-Informationen-Zentrale Freiburg +49 (0) 761 / 1 92 40

2 Hazards identification

· **Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02



GHS07

· **Signal word** Danger

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 1

Revision: 10.12.2024

Trade name: OPN-PTFE-Spray

(Contd. of page 1)

· **Hazard-determining components of labelling:** acetone· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

P305+P 351+P 338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P 233 Store in a well-ventilated place. Keep container tightly closed.

P410+P 412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with national regulations of the disposal.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

Buildup of explosive mixtures possible without sufficient ventilation.

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 67-64-1 EINECS: 204-658-1	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	>30-50%
CAS: 74-98-6 EINECS: 200-827-9	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	>10-≤20%
CAS: 106-97-8 EINECS: 203-448-7	butane, pure ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	>10-≤20%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	>5-≤10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	>5-≤10%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H332; STOT SE 3, H335	>2.5-5%

(Contd. on page 3)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 1

Revision: 10.12.2024

Trade name: OPN-PTFE-Spray

(Contd. of page 2)

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Do not eat, drink, smoke or sniff while working.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.

(Contd. on page 4)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 1

Revision: 10.12.2024

Trade name: OPN-PTFE-Spray

(Contd. of page 3)

- **Information about storage in one common storage facility:**
Do not store together with oxidising and acidic materials.
Store away from flammable substances.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

OEL	Long-term value: 1210 mg/m ³ , 500 ppm
	IOELV

74-98-6 propane

OEL	Asphx
-----	-------

106-97-8 butane, pure

OEL	Short-term value: 1000 ppm
-----	----------------------------

123-86-4 n-butyl acetate

OEL	Short-term value: 723 mg/m ³ , 150 ppm
	Long-term value: 241 mg/m ³ , 50 ppm
	IOELV

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 1

Revision: 10.12.2024

Trade name: OPN-PTFE-Spray

(Contd. of page 4)

- **Eye/face protection**
Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

- | | |
|---|-----------------------------------|
| · Physical state | Aerosol |
| · Colour: | Colourless |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| · Boiling point or initial boiling point and boiling range | -44.5°C (74-98-6 propane) |
| · Flammability | Not applicable. |
| · Lower and upper explosion limit | |
| · Lower: | 2 Vol % (106-97-8 butane, pure) |
| · Upper: | 13 Vol % (67-64-1 acetone) |
| · Flash point: | -97°C |
| · Auto-ignition temperature: | 365°C (106-97-8 butane, pure) |
| · Decomposition temperature: | Not determined. |
| · pH | Mixture is non-polar/aprotic. |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Dynamic at 20°C: | 0.7 mPas |
| · Solubility | |
| · water: | Not miscible or difficult to mix. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure at 20°C: | 8300 hPa (74-98-6 propane) |
| · Vapour pressure at 50°C: | 800 hPa |
| · Density and/or relative density | |
| · Density at 20°C: | 0.79 g/cm ³ |
| · Relative density | Not determined. |
| · Bulk density: | 790 kg/m ³ |
| · Vapour density | Not determined. |

· Other information

- | | |
|--|---|
| · Appearance: | |
| · Form: | Aerosol |
| · Important information on protection of health and environment, and on safety. | |
| · Ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Solvent content: | |
| · Organic solvents: | 83 % |
| · VOC (EC) | 83 % |
| · Solids content: | 8 % |
| · Change in condition | |
| · Evaporation rate | Not applicable. |

· Information with regard to physical hazard classes

- | | |
|---------------------|------|
| · Explosives | Void |
|---------------------|------|

(Contd. on page 6)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 1

Revision: 10.12.2024

Trade name: OPN-PTFE-Spray

(Contd. of page 5)

· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

*

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:****ATE (Acute Toxicity Estimates)**

Dermal	LD50	25622 mg/kg
Inhalative	LC50/4 h	> 78 mg/l

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

123-86-4 n-butyl acetate

Oral	LD50	13100 mg/kg (rat)
Dermal	LD50	> 5000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 21 mg/l (rat)

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	> 6800 mg/kg (rat)
Dermal	LD50	> 3400 mg/kg (rab)

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 1

Revision: 10.12.2024

Trade name: OPN-PTFE-Spray

(Contd. of page 6)

Inhalative LC50/4 h > 10.2 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---------------------------------|
| <ul style="list-style-type: none"> · UN number or ID number · ADR, IMDG, IATA | UN1950 |
| <ul style="list-style-type: none"> · UN proper shipping name · ADR, IMDG · IATA | AEROSOLS
AEROSOLS, flammable |

(Contd. on page 8)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 1

Revision: 10.12.2024

Trade name: OPN-PTFE-Spray

(Contd. of page 7)

· **Transport hazard class(es)**· **ADR**

· **Class** 2 5F
· **Label** 2.1

· **IMDG, IATA**

· **Class** 2.1
· **Label** 2.1

· **Packing group**· **ADR, IMDG, IATA** not regulated· **Environmental hazards:** Not applicable.· **Special precautions for user** Warning: Gases.· **Hazard identification number (Kemler code):** -· **EMS Number:** F-D,S-U· **Stowage Code** SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear of
living quarters.

· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1
except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· **Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· **Transport category** 2· **Tunnel restriction code** D· **IMDG**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

(Contd. on page 9)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 1

Revision: 10.12.2024

Trade name: OPN-PTFE-Spray

(Contd. of page 8)

15 Regulatory information

- **Directive 2004/42/EC**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
- None of the ingredients is listed.
- **REGULATION (EU) 2019/1148**
- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**
- None of the ingredients is listed.
- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**
- 67-64-1 | acetone
- **Regulation (EC) No 273/2004 on drug precursors**
- 67-64-1 | acetone | 3
- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
- 67-64-1 | acetone | 3
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- **Department issuing SDS:** Labor
- **Date of previous version:** 11.09.2024
- **Abbreviations and acronyms:**
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.12.2024

Version number 1

Revision: 10.12.2024

Trade name: OPN-PTFE-Spray

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 ATE: Acute toxicity estimate values
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **** Data compared to the previous version altered.***

IE