



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name	OPN Clear Coat Spray
Unique formula identifier (UFI)	XSNN-D5RF-900H-1PPU
Article number	63430
Customs tariff number	3208 20 10

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Paint, Aerosol
Uses advised against	None known.

1.3 Details of the supplier of the safety data sheet

OPN-CHEMIE GmbH

In der Au 14

57290 Neunkirchen

www.opn-chemie.de

Information Providing Area:

Competent person responsible for the safety data sheet: Barbara Angelika Gros-Petri

e-mail (competent person): baerbel.petri@opn-chemie.de

1.4 Emergency telephone number

24h Emergency information service

Poison Information Center Freiburg +49(0)761/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

*Classification according to
Regulation (EC) No. 1272/2008
[CLP]*

Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Category 3 Narcotic effects	
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Acetone; n-Butyl acetate; Xylene (reaction mass of ethylbenzene and xylene); Ethyl acetate

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0



Signal word

Danger

Hazard statements

H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection/ face protection
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor if you feel unwell
P405 - Store locked up
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible.

PBT & vPvB

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Acetone	200-662-2	67-64-1	Eye Irrit. 2 (H319)	-	-	-	01-2119471330-

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

20 - <25 %	(606-001-00-8)		STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)				49-XXXX
n-Butyl acetate 10 - <20 %	204-658-1 (607-025-00-1)	123-86-4	STOT SE 3 (H336) Flam. Liq. 3 (H226) (EUH066) [B]	-	-	-	01-2119485493-29-XXXX
Butane 10 - <20 %	203-448-7 (601-004-00-0)	106-97-8	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	01-2119474691-32-XXXX
Xylene (reaction mass of ethylbenzene and xylene) 5 - <10 %	905-588-0	RR-45541-4	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226)	-	-	-	01-2119488216-32-xxxx
Isobutane 5 - <10 %	200-857-2 (601-004-00-0)	75-28-5	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	01-2119485395-27-XXXX
Ethyl acetate 5 - <10 %	205-500-4 (607-022-00-5)	141-78-6	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	01-2119475103-46-XXXX

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Acetone	200-662-2 (606-001-00-8)	67-64-1	5800	-	-	-	-
n-Butyl acetate	204-658-1 (607-025-00-1)	123-86-4	-	-	0.74	-	-
Butane	203-448-7 (601-004-00-0)	106-97-8	-	-	-	-	-
Xylene (reaction mass of ethylbenzene and xylene)	905-588-0	RR-45541-4	3523	1999	-	19	-
Isobutane	200-857-2 (601-004-00-0)	75-28-5	-	-	-	-	-
Ethyl acetate	205-500-4 (607-022-00-5)	141-78-6	-	-	-	14.4131	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

See section 16 for more information

Chemical name	Notes
Butane - 106-97-8	C,U
Isobutane - 75-28-5	C,U

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.
---	--

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂). Hydrocarbons. Aldehydes.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Take precautionary measures against static discharges. Remove all sources of ignition. Ensure adequate ventilation. Do not breathe vapour or mist. Evacuate personnel to safe areas. Avoid contact with skin, eyes or clothing.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Keep out of drains, sewers, ditches and waterways.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Do not breathe vapour or mist. Take precautionary measures against static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Avoid contact with skin, eyes or clothing. Do not puncture or incinerate cans. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands and face before breaks and immediately after handling the product. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Store in a well-ventilated place. Keep at a temperature not exceeding 50 °C. Keep away from open flames, hot surfaces and sources of ignition. Store in accordance with the particular national regulations. Do not contaminate food or feed stuffs.

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

7.3. Specific end use(s)

Specific use(s)

Paint, Aerosol.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³
n-Butyl acetate 123-86-4	TWA: 241 mg/m ³ TWA: 50 ppm STEL: 723 mg/m ³ STEL: 150 ppm
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ S*
Ethyl acetate 141-78-6	TWA: 734 mg/m ³ TWA: 200 ppm STEL: 1468 mg/m ³ STEL: 400 ppm

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m ³	
Long term Systemic health effects worker	Inhalation	1210 mg/m ³	
n-Butyl acetate (123-86-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	300 mg/m ³	
worker Short term Systemic health effects	Inhalation	600 mg/m ³	
worker Long term	Inhalation	300 mg/m ³	

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

Local health effects			
worker Short term Local health effects	Inhalation	600 mg/m ³	
worker Long term Systemic health effects	Dermal	11 mg/kg bw/d	

Xylene (reaction mass of ethylbenzene and xylene) (RR-4541-4)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	221 mg/m ³	
worker Long term Local health effects	Inhalation	221 mg/m ³	
worker Short term Local health effects	Inhalation	442 mg/m ³	
worker Long term Systemic health effects	Dermal	212 mg/kg bw/d	

Ethyl acetate (141-78-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	63 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	1468 mg/m ³	
worker Long term Local health effects	Inhalation	734 mg/m ³	
worker Short term Local health effects	Inhalation	1468 mg/m ³	
worker Long term Systemic health effects	Inhalation	734 mg/m ³	

Derived No Effect Level (DNEL)

Acetone (67-64-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m ³	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

n-Butyl acetate (123-86-4)

Type	Exposure route	Derived No Effect Level	Safety factor
------	----------------	-------------------------	---------------

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

		(DNEL)	
Consumer Long term Systemic health effects	Inhalation	35.7 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	300 mg/m ³	
Consumer Long term Local health effects	Inhalation	35.7 mg/m ³	
Consumer Short term Local health effects	Inhalation	300 mg/m ³	
Consumer Long term Systemic health effects	Dermal	6 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	6 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	2 mg/kg bw/d	

Xylene (reaction mass of ethylbenzene and xylene) (RR-45541-4)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	65.3 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	260 mg/m ³	
Consumer Long term Local health effects	Inhalation	65.3 mg/m ³	
Consumer Short term Local health effects	Inhalation	260 mg/m ³	
Consumer Long term Systemic health effects	Dermal	125 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	12.5 mg/kg bw/d	

Ethyl acetate (141-78-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	4.5 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	37 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	734 mg/m ³	
Consumer Long term Local health effects	Inhalation	367 mg/m ³	

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

Consumer Short term Local health effects	Inhalation	734 mg/m ³	
Consumer Long term Systemic health effects	Inhalation	367 mg/m ³	

Predicted No Effect Concentration (PNEC) No information available.
(PNEC)

Predicted No Effect Concentration (PNEC)	
Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

n-Butyl acetate (123-86-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.18 mg/l
Marine water	0.018 mg/l
Freshwater - intermittent	0.36 mg/l
Sewage treatment plant	35.6 mg/l
Freshwater sediment	0.981 mg/l
Marine sediment	0.0981 mg/l
Soil	0.0903 mg/l

Xylene (reaction mass of ethylbenzene and xylene) (RR-45541-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.327 mg/l
Marine water	0.327 mg/l
Microorganisms in sewage treatment	6.58 mg/l
Freshwater sediment	12.46 mg/kg dry weight
Soil	2.31 mg/kg dry weight

Ethyl acetate (141-78-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.24 mg/l
Marine water	0.024 mg/l
Freshwater sediment	1.15 mg/kg
Marine sediment	0.115 mg/kg
Soil	0.148 mg/kg
Microorganisms in sewage treatment	650 mg/l

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection

Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

Skin and body protection	Wear appropriate personal protective clothing to prevent skin contact.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Appearance	Aerosol	
Colour	Colourless	
Odour	Solvent.	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	Not applicable, Aerosol	Not applicable, Aerosol
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	Not applicable, Aerosol	Not applicable, Aerosol
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH (as aqueous solution)	No data available	Not applicable. Insoluble in water.
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Water solubility	Insoluble in water.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	0.716 g/cm ³	
Relative vapour density	0.716	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available
VOC content	approx 664 g/L 92.8 %

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat. Do not freeze. Protect from moisture. Product cures with moisture. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Causes serious eye irritation.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	12,664.30 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	218.7471 mg/l

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
n-Butyl acetate	>10650 mg/kg (Rattus)	> 17600 mg/kg (Oryctolagus cuniculus)	=390 ppm (Rattus) 4 h
Butane	-	-	=658 g/m ³ (Rattus) 4 h
Xylene (reaction mass of ethylbenzene and xylene)	=3500 mg/kg (Rattus)	>10000 mg/kg (Oryctolagus cuniculus)	=>47635 mg/L (Rattus) 4 h = >5000 ppm (Rattus) 4 h
Isobutane	-	-	=658 mg/L (Rattus) 4 h
Ethyl acetate	=5620 mg/kg (Rattus)	> 18000 mg/kg (Oryctolagus cuniculus) > 20 mL/kg (Oryctolagus cuniculus)	LC0 29.3 mg/l air

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

n-Butyl acetate (123-86-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal		4 hours	Non-irritant

Ethyl acetate (141-78-6)

Serious eye damage/eye irritation Causes serious eye irritation.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

n-Butyl acetate (123-86-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Corneal	0.1 mL		Product score 1 Non-irritant

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Ethyl acetate (141-78-6)

Method	Species	Results
OECD Test No. 474: Mammalian Erythrocyte Micronucleus Test	in vivo Hamster	Negative
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro Salmonella typhimurium	Negative
OECD Test No. 473: In vitro Mammalian Chromosome Aberration Test	in vitro Hamster Ovary	Negative

Carcinogenicity

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
n-Butyl acetate 123-86-4	EC50: =674.7mg/L (72h, Desmodosmus subspicatus)	LC50 96 h 17 - 19 mg/L (Pimephales promelas flow-through)	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	EC50 48 h = 44 mg/L (Daphnia magna)		
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	EC50 (72hr) 2.2 mg/l (Selenastrum capricornutum)	LC50(96h) 2.6 mg/l (Oncorhynchus mykiss-OECD 203)	EC50 = 0.0084 mg/L 24 h	LC50(24h) 1 mg/l (Daphnia magna-OECD 202)		
Ethyl acetate 141-78-6	EC50: =3300mg/L (48h, Desmodosmus subspicatus)	LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss) LC50: 220 - 250mg/L	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50: =560mg/L (48h, Daphnia magna)		

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

		(96h, Pimephales promelas)				
--	--	----------------------------------	--	--	--	--

12.2. Persistence and degradability

Persistence and degradability No information available.

Acetone (67-64-1)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

n-Butyl acetate (123-86-4)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	83%	Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation No information available.

Component Information

Chemical name	Partition coefficient
Acetone	-0.24
n-Butyl acetate	2.3
Butane	2.31
Xylene (reaction mass of ethylbenzene and xylene)	3.15
Isobutane	2.8
Ethyl acetate	0.73

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Acetone	The substance is not PBT / vPvB
n-Butyl acetate	The substance is not PBT / vPvB
Butane	The substance is not PBT / vPvB
Xylene (reaction mass of ethylbenzene and xylene)	The substance is not PBT / vPvB
Isobutane	The substance is not PBT / vPvB
Ethyl acetate	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	16 05 04* gases in pressure containers (including halons) containing dangerous substances 15 01 04 metallic packaging
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2
Labels	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2, (D)
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	190, 327, 344, 625
Classification code	5F
Tunnel restriction code	(D)
Limited quantity (LQ)	1 L

IMDG

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1, (0°C c.c.)
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ)	See SP277
EmS-No.	F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	A145, A167, A802
Limited quantity (LQ)	30 kg G
ERG Code	10L

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. This product contains:

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted	Registration
Acetone - 67-64-1	Regulated		

National regulations

France

Occupational Illnesses (R-463-3, France)

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

Chemical name	French RG number
Acetone 67-64-1	RG 84
n-Butyl acetate 123-86-4	RG 84
Butane 106-97-8	RG 84
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	RG 4bis, RG 84
Isobutane 75-28-5	RG 84
Ethyl acetate 141-78-6	RG 84

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) obviously hazardous to water (WGK 2)

TRGS - 510 Storage Class Storage Class 2B : Aerosols

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands - List of Carcinogens
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	Development (Category 2)

Denmark

Registration number(s) (P-no.) No information available

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

Notes relating to the identification, classification and labelling of substances

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.)

Press. Gas (Liq.)

Press. Gas (Ref. Liq.)

Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value

BGW

Biological limit value

Ceiling Maximum limit value

SK*

Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGl(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications

Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008. This SDS is for generic information purposes and does not reflect required country specific information for OEL.

OPN Clear Coat Spray

Date of compilation: 20.06.2024

Revision: 25.07.2025

Revision number: 1.0

Prepared By Product Safety & Regulatory Affairs

Revision date 20-Jun-2024

Revision note First time release

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet