

Printing date 29.01.2018 Version number 20 Revision: 29.01.2018

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

·Trade name: OPN-Battery Terminal Grease Spray

·Article number: 61071

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Relevant identified uses industrial use, professional use
- · Application of the substance / the mixture Preservative

· Uses advised against:

consumer use (private households)

Do not use for products that are intended for contact with food - exclude food contact.

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

OPN-CHEMIE OTTO PETRI GMBH

In der Au 14

D-57290 Neunkirchen/Germany

Tel.: +49 (0) 2735 / 7725-0 Fax: +49 (0) 2735 / 7725-90 E-Mail: info@opn-chemie.de Web: www.opn-chemie.de

· Further information obtainable from:

Safety data sheets Mrs. Barbara Angelika Gros-Petri

Tel.: +49 (0) 2735 / 7725-20 E-Mail: baerbel.petri@opn-chemie.de

· 1.4 24 hours Emergency telephone number:

Vergiftungs-Informations-Zentrale Freiburg +49 (0) 761 / 192 40

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Danger
- $\cdot \ \textbf{Hazard-determining components of labelling:}$

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane

(Contd. on page 2)

Printing date 29.01.2018 Version number 20 Revision: 29.01.2018

Trade name: OPN-Battery Terminal Grease Spray

(Contd. of page 1)

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
- P501 Dispose of contents/container to hazardous or special waste.

#### · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- $\cdot$  **vPvB:** Not applicable.

# **SECTION3: Composition/information on ingredients**

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes	20-<25%
Reg.nr.: 01-2119475515-33-xxxx	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	
EC number: 921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5	20-<25%
Reg.nr.: 01-2119475514-35-xxxx	% n-hexane	
	<ul> <li>Flam. Liq. 2, H225;</li> <li>Asp. Tox. 1, H304;</li> <li>Aquatic Chronic 2, H411;</li> <li>Skin Irrit. 2, H315; STOT SE 3, H336</li> </ul>	
CAS: 75-28-5	isobutane	10-<20%
EINECS: 200-857-2	♦ Flam. Gas 1, H220; ♦ Press. Gas C, H280	
Reg.nr.: 01-2119485395-27-xxxx		
CAS: 74-98-6	propane	5-<10%
EINECS: 200-827-9	♦ Flam. Gas 1, H220; ♦ Press. Gas C, H280	
Reg.nr.: 01-2119486944-21-xxxx		
CAS: 106-97-8	butane	1-<2.5%
EINECS: 203-448-7	Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119474691-32-xxxx		
4 1 1144 1 1 0 44 E 41	ryanding of the listed beyond abuses refer to section 16	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

- GB

Printing date 29.01.2018 Version number 20 Revision: 29.01.2018

**Trade name: OPN-Battery Terminal Grease Spray** 

(Contd. of page 2)

### **SECTION4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

Dizziness

Dizziness

Coughing

Nausea

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary oedema.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### **SECTION6: Accidental release measures**

# $\cdot$ 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

• 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 29.01.2018 Version number 20 Revision: 29.01.2018

**Trade name: OPN-Battery Terminal Grease Spray** 

(Contd. of page 3)

• 6.4 Reference to other sections See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

#### **CAS: 106-97-8 butane**

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Recommended filter device for short term use: Filter AX
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.45 mm

· Penetration time of glove material

≥240 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2018 Version number 20 Revision: 29.01.2018

Trade name: OPN-Battery Terminal Grease Spray

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

# **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Colour: Blue
• Odour: Petrol-like

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: $< 0$ $^{\circ}\mathrm{C}$		
· Flash point:	Not applicable, as aerosol.	
· Ignition temperature:	>200 °C	
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Density at 20 °C:	0.6978 g/cm³	
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
· Viscosity:		

Not determined.

Not determined.

71.3 %

497.8 g/l

Kinematic: Organic solvents: VOC (EC)

**Dynamic:** 

- Solids content: 0.0 %
- **9.2 Other information** No further relevant information available.

# **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Aldehyde

Carbon monoxide and carbon dioxide

Printing date 29.01.2018 Version number 20 Revision: 29.01.2018

**Trade name: OPN-Battery Terminal Grease Spray** 

(Contd. of page 5)

### **SECTION11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

#### **ATE (Acute Toxicity Estimates)**

Inhalative LC50/4 h 238 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

#### **SECTION12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

	· European waste catalogue	
	16 05 04*	gases in pressure containers (including halons) containing hazardous substances
ſ	15 01 04	metallic packaging

(Contd. on page 7

Printing date 29.01.2018 Version number 20 Revision: 29.01.2018

Trade name: OPN-Battery Terminal Grease Spray

(Contd. of page 6)

- Uncleaned packaging:
  Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR/RID/ADN, IMDG, IATA	UN1950
	0111930
14.2 UN proper shipping name ADR/RID/ADN	UN1950 AEROSOLS, ENVIRONMENTALL
ADN/RID/ADIN	HAZARDOUS
IMDG	AEROSOLS, MARINE POLLUTANT
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR/RID/ADN	
<b>₹</b>	
Class	2 5F Gases.
Label	2.1
IMDG	
Av.	
<b>1</b>	
	2.1
Class Label	2.1 2.1
	2.1
IATA	
Class	2.1
Label	2.1
14.4 Packing group	
ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substance
	Solvent Naphta
Marine pollutant:	Yes
~	Symbol (fish and tree)
Special marking (ADR/RID/ADN):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW12 For A FROSOL S with a maximum capacity of
	SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity about
	1 litre: Category B. For WASTE AEROSOLS: Catego
	C, Clear of living quarters.
<b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of
	litre: Segregation as for class 9. Stow "separated from
	class 1 except for division 1.4. For AEROSOLS with a

(Contd. on page 8)

Printing date 29.01.2018 Version number 20 Revision: 29.01.2018

Trade name: OPN-Battery Terminal Grease Spray

	(Contd. of page
	capacity above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to A1	nnex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
_ <del>_</del>	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALL HAZARDOUS

# **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

(Contd. on page 9)

Printing date 29.01.2018 Version number 20 Revision: 29.01.2018

Trade name: OPN-Battery Terminal Grease Spray

(Contd. of page 8)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* \* Data compared to the previous version altered.

GB