

OPN-CHEMIE OTTO PETRI GmbH

Produktion techn. Aerosole - Sprays

In der Au 14, D-57290 Neunkirchen / Germany

Phone: +49 (0) 27 35 / 77 25-0 Fax: +49 (0) 27 35 / 77 25-90

www.opn-chemie.de info@opn-chemie.de



Product Information

OPN-Universal Marking Spray

360° special valve - sprayable in all positions -

"Day-glow colors" or "neon colors":

Art.-No. 63500 - yellow, Art.-No. 63501 - red, Art.-No. 63510 - yellow-orange,

Art.-No. 63502 - red-orange, Art.-No. 63503 - orange, Art.-No. 63504 - green,

Art.-No. 63505 - pink, Art.-No. 63506 - blue

„Normal colors“:

Art.-No. 63509 - yellow, Art.-No. 63507 - orange, Art.-No. 63508 - blue, Art.-No. 63511 - green,

Art.-No. 63512 - red, Art.-No. 63513 - black, Art.-No. 63514 - white

Properties:

- **universally suitable for floor and wall marking**
- **low-odor** special marking color with **high opacity** and **drying in just about 3 minutes** therefore can be processed quickly and time-saving
- **high "luminosity"** therefore very good and fast to recognize on dark ground
- **can also be processed on damp ground**
- **weatherproof**
- not gasoline resistant

Application Range:

- **developed for universal use in forestry, woodworking industry, civil engineering, metalworking industry etc.**
- for fast, clean, permanent marking and marking on damp and dry **wood, steel, concrete, asphalt, masonry, paper, bricks, paving, etc.**
- **1 additional spray nozzle included, so that fine and coarse marking is easily possible**

Application:

Read processing instructions completely before starting work.

Our information are recommendations based on our experience. We accept no liability for any damage without tests concerning suitability for the specific application, without preliminary trials and if the products is misused. Under the cap you will find the second spray nozzle (see label opposite side below). When used, the can should be at "room temperature". **Shake strongly before use and after each spray break until the stirring ball moves freely.** The area to be sprayed has to be dry (possibly damp, but not wet), free of loose dirt and free of grease. Cover surfaces that are not to be sprayed and apply targeted from approx. 15 - 20 cm. Color is not gasoline resistant. **Only for professional use! Always observe safety data sheet before use.**

Delivery information: Art.-No. see above

Spray: 500 ml Content, Packing Unit: 12 Cans/Carton

Observe the information on the label and of the EC-safety data sheet!

Our technical information has been compiled carefully to the best of our knowledge. Because of the many possible influences during processing and use of the products they do not relieve the processor of its own, conscientious exams! A legally binding assurance of certain properties or of the suitability for a particular purpose can not be derived from our information. Existing laws and regulations must be checked and observed from the processor of our products before use in his own responsibility.

All text passages are subject to the copyright of OPN-CHEMIE OTTO PETRI GmbH.